

SHARPEN YOUR CUTTING EDGE!

Upgrade to Hypertherm's Duramax retrofit torch

5 times more durable

 Proprietary, fiber-reinforced torch handle is 5 times more impact resistant and 20% more heat resistant to withstand your toughest metal-cutting applications.*

More reliable arc-starting


 Spring Start™ electrode technology eliminates moving parts in the torch for more reliable arc-starting.*

Up to 55% longer consumable life

 Conical Flow[™] nozzle and spring electrode give you up to 55% more consumable life for up to a 30% reduction in consumable costs.*

Easy plug-and-play upgrade

- Duramax RT torches use the same Easy Torch Removal (ETR) connection as your standard torch which makes retrofitting to a new Duramax torch simple.
- * When compared with standard T60/T80/T100 torches and/or consumables for Powermax1000/1250/1650.



"We were using 5 sets of tips per week, now with the new retrofit torch we use the system more and are using only 1 set per week. The consumable savings will pay for a new system!"

- Travis, Manufacturing Foreman, JMH Trailers

COMPATIBLE WITH

Powermax1000® Powermax1250® Powermax1650®



Duramax™H4:11

Handheld retrofit torch

Torch neck is **20% slimmer** for greater arc visibility and increased accessibility





Proprietary, fiber-reinforced torch handle is 20% more heat resistant and 5 times more impact resistant than your standard Powermax torch

Ergonomic torch for noticeably easier handling

Square handle grip for **more control**

Duramax™M4?11

Mechanized retrofit torch

- Full-length torch 380 mm (15")
- Features a removable gear rack
- Converts to a mini torch configuration for improved cutting accessibility in robotic applications

Full-length machine torch converts to a mini-machine torch

New spring strain-relief design to improve bend reliability by 10 times

Enhanced trigger for a smooth action, **more control** and **easy activation**

MAX43 systems.

More abrasion-resistant torch lead

More convenient – Now you can consolidate consumables across multiple product families because Duramax torches are now available for Powermax1000, Powermax1250, Powermax1650, Powermax65, Powermax85, Powermax105, Powermax600, Powermax800, Powermax900, MAX42 and

Easy Torch Removal (ETR) connection
– makes Duramax retrofit torches easy plug-and-play upgrades



PARTS LIST

Duramax retrofit torches

Part number	Description	Compatible system(s)
228788†	Duramax HRT Hand Torch Assembly with 7.6 m (25') Leads	Powermax1000, Powermax1250, Powermax1650
228789 [†]	Duramax HRT Hand Torch Assembly with 15.2 m (50') Leads	Powermax1000, Powermax1250, Powermax1650
228807 [†]	Duramax HRTs Hand Torch Assembly with 7.6 m (25') Leads	Powermax1000, Powermax1250, Powermax1650
228808†	Duramax HRTs Hand Torch Assembly with 15.2 m (50') Leads	Powermax1000, Powermax1250, Powermax1650
228790†	Duramax MRT Machine Torch Assembly with 7.6 m (25') Leads	Powermax1000, Powermax1250, Powermax1650
228791 [†]	Duramax MRT Machine Torch Assembly with 15.2 m (50') Leads	Powermax1000, Powermax1250, Powermax1650

[†] Includes a variety of Duramax consumables, new operator manual with cut charts and new consumables sticker for your system

Duramax consumables

Part number	General part description	Amperage compatibility
220857	Swirl ring, all processes except handheld FineCut and 100 A / 105 A	40 A - 85 A
220994	Swirl ring, 105 A	100 A - 105 A
220947	Swirl ring, handheld FineCut	40 A - 45 A
220842	Standard Duramax Electrode	40 A - 105 A
220777	CopperPlus Electrode*	40 A - 105 A
220941	Nozzle, 45 A	40 A - 55 A
220819	Nozzle, 65 A	60 A - 65 A
220816	Nozzle, 85 A	80 A - 85 A
220990	Nozzle, 105 A	100 A - 105 A
220930	Nozzle, FineCut	40 A - 45 A
220797	Nozzle, 65 A / 85 A gouging	40 A - 85 A
220991	Nozzle, 105 A gouging	100 A - 105 A
220854	Retaining cap	40 A - 105 A
220953	Retaining cap, ohmic	40 A - 105 A
220818	Shield, 65 A / 85 A drag-cutting	40 A - 85 A
220992	Shield, 105 A drag-cutting	100 A - 105 A
220817	Shield, 65 A / 85 A mechanized	40 A - 85 A
220993	Shield, 105 A mechanized	100 A - 105 A
220798	Shield, gouging	40 A - 105 A
220948	Shield, FineCut ohmic	40 A - 45 A
220955	Deflector, mechanized	40 A - 105 A
220931	Deflector, handheld FineCut	40 A - 45 A

^{*} For more information about CopperPlus, visit www.hypertherm.com/upgrades

Kits and accessories

Part number	Description
850910	All-in-one consumable kit - compatible with HRT/HRTs and Powermax1000 handheld
850900	All-in-one consumable kit - compatible with MRT and Powermax1000 mechanized
850890	All-in-one consumable kit – compatible with HRT/HRTs and Powermax1250 handheld
850880	All-in-one consumable kit - compatible with MRT and Powermax1250 mechanized
850992	All-in-one consumable kit – compatible with HRT/HRTs and Powermax1650 handheld
850985	All-in-one consumable kit - compatible with MRT and Powermax1650 mechanized
850930	FineCut consumable kit - compatible with all HRT/HRTs handheld torches
850920	FineCut consumable kit - compatible with all MRT mechanized torches
024548	Leather lead cover available in 7.6 m (25') sections
127102	Circle cutting guide, basic kit
027668	Circle cutting guide, deluxe kit
128647	Air filtration kit

Hypertherm[®]

Cut with confidence®

Hypertherm, Duramax, Powermax, FineCut, Duramax, Spring Start and Conical Flow are trademarks of Hypertherm, Inc. and may be registered in the United States and/or other countries. All other trademarks are the properties of their respective owners.

Data shown are the product of controlled testing in Hypertherm laboratories. Contact Hypertherm for a complete written description of test procedures.







1 year torch and lead warranty





^{© 5/2012} Hypertherm, Inc. Revision 2 894240